



Crest Technologies Pty Ltd  
 46/41-49 Norcal Rd Nunawading 3131 Australia  
 Tel: (03) 9873 8830 Fax: (03) 9873 8799  
 Email: sales@cresttech.com.au  
 Web: http://www.cresttech.com.au

# CRYSTAL OSCILLATOR

Series HCO-6T, TEMPERATURE COMPENSATED CRYSTAL OSCILLATOR (TCXO)

## APPLICATION

- Mobile communication, Avionics,
- Test Equipment, Electronic instruments



## ELECTRICAL SPECIFICATIONS

Items		TFT210	TFT230	TFT250	TFT270	TFT300
Frequency Range (MHz)		1~32	30~95	90~155	150~210	200~1500
F-T stability (ppm)		±0.5~±5			±1~±10	
Operating Temperature (°C)		-10~60	0~70	-20~+70	-40~+70	-50~+85
Storage Temperature (°C)		-55~+120				
Power	Voltage (Vdc)	+3.3 +5.0 +12				
	Current (mA)	2~20				
Output	Waveform	Sine/pulse			Sine	
	Impedance	50Ω/100Ω			50Ω	
	Level	(pulse):TTL/HCMOS			(Sine):≥1.5vP-P/50Ω	
	Type	(pins):SMA			SMA	
Aging/year (ppm)		±1~±3				
Frequency trim (ppm)		±1~±5/ (mechanical or electrical)				
F-V Stability		(3~5)×10 <sup>-7</sup> (3.3V±5%,5V±10%,12V±10%)				
Dimension (mm)		18.5x12x(8~10) 20.8x13.2x(8~10) 25x15x10 30x20x10 40x25x15 44x27x19 50.8x50.8x18 91x56x20				

