



L-XXXXXCT Bin Code List

Forward Voltage Bin Code(0.1V Range),Unit:V

Bin Code	Min	Max
1	1.55	1.75
2	1.65	1.85
3	1.75	1.95
4	1.85	2.05
5	1.95	2.15
6	2.05	2.25
7	2.15	2.35
8	2.25	2.45
9	2.35	2.55
10	2.45	2.65
11	2.55	2.75
12	2.65	2.85
13	2.75	2.95
14	2.85	3.05
15	2.95	3.15
16	3.05	3.25
17	3.15	3.35
18	3.25	3.45
19	3.35	3.55
20	3.45	3.65
21	3.55	3.75
22	3.65	3.85
23	3.75	3.95
24	3.85	4.05

Forward Voltage Bin Code(0.15V Range),Unit:V

Bin Code	Min	Max
J1	1.65	1.90
J2	1.80	2.05
J3	1.95	2.20
J4	2.10	2.35
J5	2.25	2.50
J6	2.40	2.65
J7	2.55	2.80
J8	2.70	2.95
J9	2.85	3.10
J10	3.00	3.25
J11	3.15	3.40
J12	3.30	3.55
J13	3.45	3.70
J14	3.60	3.85
K1	1.70	1.95
K2	1.85	2.00
K3	2.00	2.25
K4	2.15	2.40
K5	2.30	2.55
K6	2.45	2.70
K7	2.60	2.85
K8	2.80	3.00
K9	2.95	3.15
K10	3.05	3.30
K11	3.20	3.45
K12	3.35	3.60
K13	3.50	3.75
K14	3.65	3.90

Including test tolerance

Luminous Intensity Bin Code,Unit:mcd

Bin Code	Min	Max
A	0.10	0.20
B	0.16	0.25
C	0.25	0.50
D	0.40	0.80
E	0.63	1.25
F	1.00	2.00
G	1.60	3.20
H	2.50	5.00
J	4.00	8.00
K	6.30	12.50
L	10.00	20.00
M	16.00	32.00
N	25.00	50.00
P	40.00	80.00
Q	63.00	125.00
R	100.00	200.00
S	160.00	320.00
T	250.00	500.00
U	400.00	800.00
V	630.00	1250.00
W	1000.00	2000.00
X	1600.00	3200.00
Y	2500.00	5000.00

Including test tolerance

Dominant Wavelength Bin Code,Unit:nm

Bin Code	Min	Max
AC	464.0	471.0
AD	469.0	476.0
GA	566.0	571.0
GB	569.0	574.0
YA	586.0	591.0
YB	589.0	594.0