


| PIN NO. | SYMBOL |
|---------|--------|
| 1 | VDD |
| 2 | VSS |
| 3 | CS1B |
| 4 | CS2 |
| 5 | RES |
| 6 | A0 |
| 7 | R/W |
| 8 | E |
| 9 | DB0 |
| 10 | DB1 |
| 11 | DB2 |
| 12 | DB3 |
| 13 | DB4 |
| 14 | DB5 |
| 15 | DB6 |
| 16 | DB7 |
| 17 | C86 |
| 18 | P/S |

| | | |
|---|------------------------|------------------------|
| 1 | Lcd Type | FSTN White |
| 2 | Viewing Direction | 6H |
| 3 | Drive Method | 1/64 DUTY,1/9 BIAS |
| 4 | Operating Voltage(LCD) | 9.1V |
| 5 | Polsrizer Mode | Positive Transflective |
| 6 | Operating Temperature | -20°C ~ 70°C |
| 7 | Storage Temperature | -30°C ~ 80°C |



The non-specified tolerance of dimension is ±0.2 mm .

| | | |
|------------|--------------|-----------------------------------|
| SCALE: 3/2 | REV: 0 | 華凌光電股份有限公司 WINSTAR DISPLAY CO. |
| UNIT: mm | PAGE: 1/1 | |
| APPROVE | | MODEL WX12864T1-TFH# |
| CHECK | | TITLE LCD DRAWING |
| DRAW | 何群英 7/03/08' | DWG NO. T-970710 |